

Finger Tight 2,500 psi Fitting

The Diba 10-32 Type S ferrule and Click-N-Seal® fittings, when used together, provide a quick and simple method to connect 1/16" OD PEEK tubing into a 10-32 HPLC type threaded port without the use of tools. This connection system has a pressure rating up to 2,500 psi, making it ideal for many HPLC applications.

Benefits

- True finger-tight connection, cannot under-tighten or over-tighten
- Repeatable tube compression
- Quick and easy to use
- No tools required
- Suitable for Diba tubing assemblies
- Compact design for space constrained applications

Features

- No tools required to fix ferrule onto tube
- Torque limited PEEK 10-32 threaded Click-N-Seal® nut
- Ferrule permanently fixed onto tube
- Pressure rating up to 2,500 psi
- PEEK ferrule insert with 316 stainless steel case
- Retains 1/16" OD PEEK tube



North America/ROW
Diba Industries Inc.
4 Precision Road
Danbury, CT 06810 USA
Tel: +1 (203)-744-0773
Fax: +1 (203)-744-0663
salesdept@dibaind.com

Europe
Diba Industries Ltd.
2 College Park
Coldhams Lane
Cambridge, CB1 3HD, UK
Tel: +44 (0) 1223 472801
Fax: +44 (0) 1223 416787
sales@dibaind.com

China
Diba Industries Inc.
Halma International Ltd.
Shanghai Representative Office
Room 1106, Metro Plaza, No555
Lou Shan Guan Road,
Shanghai, PRC 200051, CHINA
Tel: +86-21-6016-7622
Fax: +86-21-5206-8191
chinasales@dibaind.com

www.dibaind.com

A HALMA COMPANY